

ProPlex™

CABLES FOR ETC SYSTEMS

	<i>ProPlex</i> Cable	Application
DMX	<i>ProPlex</i> PC244T	Installation DMX Cable - 2 pair, 0.25mm ² (24 AWG) data cable with individually shielded pairs, CM CMH.
	<i>ProPlex</i> PC244TP	Plenum installation DMX cable - 2 pair, 0.25mm ² (24 AWG) data cable with individually shielded pairs, CMP.
	<i>ProPlex</i> PC224T	Installation (indoor/outdoor) / medium duty portable DMX cable - 2 pair, 0.34mm ² (22 AWG) data cable with overall shielded pairs, CL2 FT1, UV and fungus resistant.
	<i>ProPlex</i> PC224P	Extra heavy-duty portable (indoor/outdoor) DMX cable - 2 pair, 0.34mm ² (22 AWG) data cable with overall shielded pairs.
RFU	<i>ProPlex</i> PC248T	Installation RFU cable - 4 pair, 0.25mm ² (24 AWG) data cable with individually shielded pairs, CM CMH.
	<i>ProPlex</i> PC248TP	Plenum installation RFU cable - 4 pair, 0.25mm ² (24 AWG) data cable with individually shielded pairs, CMP.
	<i>ProPlex</i> PC226T	Installation / portable (indoor/outdoor) medium duty RFU cable - 3 pair, 0.34mm ² (22AWG) data cable with overall shielded pairs, CL2 FT1, UV and fungus resistant.
ETC Link	<i>ProPlex</i> PC248T	Installation RFU cable - 4 pair, 0.25mm ² (24 AWG) data cable with individually shielded pairs, CM CMH.
	<i>ProPlex</i> PC248TP	Plenum installation RFU cable - 4 pair, 0.25mm ² (24 AWG) data cable with individually shielded pairs, CMP.
	<i>ProPlex</i> PC226T	Installation / portable (indoor/outdoor) medium duty RFU cable - 3 pair, 0.34mm ² (22AWG) data cable with overall shielded pairs, CL2 FT1, UV and fungus resistant.
CAT5	<i>ProPlex</i> PCCAT5P	CAT5 SFTP requirements. Extra heavy-duty portable patch cable - 4 pair, 0.14mm ² (26 AWG), 100 Ohm SFTP round cable, overall double shield, jacketed in black UV resistant Polyurethane. Designed to the IEC 61156 and TIA/EIA 568-B CAT5 requirements. Meets all CAT5 horizontal specs up to 85 meters; all CAT5 horizontal specs except attenuation up to 100 meters.
CAT5E	<i>ProPlex</i> PCCAT5EP	CAT5E SFTP requirements. Extra heavy-duty portable patch cable - 4 pair, 0.25mm ² (24 AWG), 100 Ohm SFTP round patch cable, double shielded with kevlar reinforcement strands, jacketed in black UV resistant Polyurethane. Designed to the ISO / IEC 11801 CAT5E requirements. Meets all CAT5 horizontal specs up to 75 meters; all CAT5 horizontal specs except attenuation up to 100 meters.
	<i>ProPlex</i> PCCAT5EUTPP	CAT5E UTP requirements. Extra heavy-duty portable patch cable - 4 pair, 0.25mm ² (24 AWG), 100 Ohm UTP round cable, assembled with kevlar reinforcement strands, jacketed in Black UV resistant Polyurethane. Designed to the IEC 61156-6 and TIA/EIA 568-B.2 CAT5E requirements. Meets all CAT5 horizontal specs up to 85 meters; all CAT5 horizontal specs except attenuation up to 100 meters.
ETC Unison Link Power	<i>ProPlex</i> PCLP1PT	Installation with non-metallic conduit - 1 pair, 1.5 mm ² (16 AWG) twisted with 0.34mm ² (22 AWG) ground, CL3 FT1.
	<i>ProPlex</i> PCLP1PTP	Plenum installation - 1 pair, 1.5 mm ² (16 AWG) twisted with 0.34mm ² (22 AWG) ground, CL3P FT1.
ETC Unison Link +Display	<i>ProPlex</i> PCLP2PT	Installation plus LCD display panel - 2 pair, 1.5 mm ² (16 AWG) twisted with 2.5mm ² (14 AWG) ground, CL3 FT1.
	<i>ProPlex</i> PCLP2PTP	Plenum installation plus LCD display panel - 2 pair, 1.5 mm ² (16 AWG) twisted with 2.5mm ² (14 AWG) ground, CL3P FT1.

LITPPXETC-061710



LOS ANGELES

10643 Glenoaks Blvd.
Pacoima, CA 91331
USA

Tel: +1 818.899.8818
Fax: +1 818.899.8813

LONDON

21 Armstrong Way
Southall
UB2 4SD England

Tel: +44 (0)20.8574.9700
Fax: +44 (0)20.8574.9701

NEW YORK

100 Asia Place
Carlstadt, NJ 07072
USA

Tel: +1 201.896.8600
Fax: +1 201.896.8601

BEIJING

No. 309, Building 6
Sanlitun Nanlu
Chaoyang District
Beijing, China 100027

Tel: +86 10.8492.1587
Fax: +86 10.8492.7635

TORONTO

409 Saddler St. West
Box 654, Durham
Ontario N0G-1R0

Tel: +1 519.369.9990
Fax: +1 519.369.9992